

DECLARATION OF PERFORMANCE

No 0010_Vidiwall_1_Mann_12,5_2015-12-10

1. Unique identification code of the product-type: GF-W2 - Knauf Vidiwall 1 Mann 12,5

2. Intended use/es: Gypsum fibre boards in buildings

3. Manufacturer: Knauf Gips KG, Am Bahnhof 7, D-97346 Iphofen, Germany

Tel. +49-9323-31-0, Fax +49-9323-31-277, e-mail Zentrale@knauf.de

4. Authorised representative: Not relevant

5. System/s of AVCP: System 3 (reaction to fire) and 4 (for other uses)

6. a) Harmonised standard: EN 15283-2:2008+A1:2009-08

Notified body/ies: MPA Stuttgart (NB 0672) performed the testing of the reaction to fire.

Determination of product type on the basis of type testing and factory

production control by manufacturer.

6. b) European Assessment Document: Not relevant / European Technical Assessment: Not relevant

Technical Assessment Body: Not relevant / Notified body/ies: Not relevant

7. Declared performance/s:

Essential characteristics	Performance
Flexural strength - F	pass (≥ 5,5 N/mm²)
Shear strength - ↑↓	NPD
Reaction to fire - R2F	A2-s1,d0
Water vapour resistance factor - μ	15 (EN ISO 12572)
Thermal conductivity – λ	≤ 0,30 W/(m⋅K) (EN 12664)
Dangerous substances - DS	NPD
Airborne sound insulation* - R	see manufacturer's literature
Acoustic absorption* - α	
Impact Resistance* - →I	
* These characteristics are system dependent and should b	pe provided in producer's literature based upon intended use.

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: ppa. Dr. Markus Biebl (Head of Research & Development Knauf Group)

At Iphofen, on 2015-12-10