



DECLARATION OF PERFORMANCE

No 0010_MineralAktiv_Scheibenputz_3,0_2015-12-15

1. Unique identification code of the product-type: **V1 - W2 - 0,3 MPa - 0,7 W/(m·K) - A2-s1,d0 – Knauf MineralAktiv Scheibenputz 3,0 mm**
2. Intended use/es: **On external walls, ceilings, columns and partitions**
3. Manufacturer: **Knauf Gips KG, Am Bahnhof 7, D-97346 Iphofen, Germany
Tel. +49-9323-31-0, Fax +49-9323-31-277, e-mail Zentrale@knauf.de**
4. Authorised representative: **Not relevant**
5. System/s of AVCP: **System 3**
6. a) Harmonised standard: **EN 15824:2009-07**
Notified body/ies: **Prüfinstitut Hoch (NB 1508) performed the testing of the reaction to fire. Determination of product type on the basis of type testing and factory production control by manufacturer.**
6. b) European Assessment Document: **Not relevant** / European Technical Assessment: **Not relevant**
Technical Assessment Body: **Not relevant** / Notified body/ies: **Not relevant**
7. Declared performance/s:

Essential characteristics	Performance
Water vapour permeability	V ₁
Water absorption	W ₂
Adhesion	≥ 0,3 MPa
Durability	NPD
Thermal conductivity - λ	0,7 W/(m·K)
Reaction to fire	A2-s1,d0
Dangerous substances	NPD

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not relevant**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
ppa. Dr. Markus Biebl
(Head of Research & Development Knauf Group)



At Iphofen, on 2015-12-15