



## DECLARATION OF PERFORMANCE

No 0010\_Raumklima\_Spritzputz\_2014-11-18

1. Unique identification code of the product-type: **V1 – 0,3 MPa –  $\lambda = 0,5 \text{ W/(m}\cdot\text{K)}$  – A1**
2. Intended use/es: **On internal walls, ceilings, columns and partitions**
3. Manufacturer: **Knauf Gips KG, Am Bahnhof 7, D-97346 Iphofen, Germany  
Tel. +499323 31-0, Fax +499323 31-277, e-mail Zentrale@knauf.de**
4. Authorised representative: **Not relevant**
5. System/s of AVCP: **System 3**
6. a) Harmonised standard: **EN 15824:2009-07**  
Notified body/ies: **MFPA Leipzig GmbH (NB 0800) performed the testing of the reaction to fire. Determination of product type on the basis of type testing and factory production control by manufacturer.**
6. b) European Assessment Document: **Not relevant** / European Technical Assessment: **Not relevant**  
Technical Assessment Body: **Not relevant** / Notified body/ies: **Not relevant**
7. Declared performance/s:

<b>Essential characteristics</b>	<b>Performance</b>
Water vapour permeability	V <sub>1</sub>
Water absorption	NPD
Adhesion	≥ 0,3 MPa
Durability	NPD
Thermal conductivity	$\lambda = 0,5 \text{ W/(m}\cdot\text{K)}$
Reaction to fire	A1
Dangerous substances	NPD

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **Not relevant**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
ppa. Dr. Markus Biebl  
(Head of Research & Development Knauf Group)

At Iphofen, on 2014-11-18

  
-----