

DECLARATION OF PERFORMANCE

No 0010_Spachtel_C_2017-08-21

1. Unique identification code of the product-type: 0,3MPa – A2-s1,d0 – Knauf Spachtel C

2. Intended use/es: On internal walls, ceilings, columns and partitions

3. Manufacturer: Knauf Gips KG | Am Bahnhof 7 | D-97346 lphofen

Tel: +49 (9323) 31-0 Fax: +49 (9323) 31-277 e-mail: zentrale@knauf.de

4. Authorised representative: not relevant5. System/s of AVCP: System 4

Klicken Sie hier, um Text einzugeben.

6. a) Harmonised standard: EN 15824:2009-07

Notified body/ies:

6. b) European Assessment Document:

European Technical Assessment:

Technical Assessment Body:

Notified body/ies:

not relevant
not relevant
not relevant

7. Declared performance/s:

Essential characteristics		Performance
Water vapour permeability		NPD
Water absorption		NPD
Adhesion		≥ 0,30 MPa
Durability		NPD
Thermal conductivity	λ	NPD
Reaction to fire		A2-s1,d0
Dangerous substances		NPD

^{*} These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use. Performance declared is for the System of which the product is a part.

8. Appropriate Technical Documentation

and/or Specific Technical Documentation: not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Iphofen, 2017-08-21

i. V. Dr. Wolfgang Rümler

(Head of Research & Development D/CH | Knauf Gips KG)

i. V. Dr. Norbert Wings

(Head of Product Development, Competence Centre Readymix Compounds | Knauf Gips KG)