

## **DECLARATION OF PERFORMANCE**

No. 0022\_Flexkleber eXtra\_2015-04-20

1. Unique identification code of the product-type: C2 TE S1 - Knauf Flexkleber eXtra

2. Intended use/es: Deformable cementitious mortar for increased requirements with

reduced slipping and extended open time for indoors and outdoors

3. Manufacturer: Knauf Bauprodukte GmbH & Co. KG, Am Bahnhof 7, D-97346 lphofen

Tel. +499323 31-0, Fax +499323 31-277, E-Mail Zentrale@Knauf.de

4. Authorised representative: **Not relevant** 

5. System(s) for evaluating and verifying constancy of performance: **System 3** 

6. a) Harmonised standard: **EN 12004:2014-02** 

Notified body/ies: TÜV Rheinland LGA Bautechnik GmbH (NB 0780) has conducted type

testing according to system 3 and issued the following: according to

a. lilles

classification report: 94623634 C2 TE S1

6. b) European Assessment Document: Not relevant / European Technical Assessment: Not relevant

Technical Assessment Body: Not relevant / Notified body/ies: Not relevant

7. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	E (WFT)
Release of danqerous substances	NPD
High initial tensile adhesion strength after dry storage	≥ 1,0 N/mm²
Extended open time: tensile adhesion strength	≥ 0,5 N/mm²
High tensile adhesion strength after heat ageing	≥ 1,0 N/mm²
High tensile adhesion strength after water immersion	≥ 1,0 N/mm²
High tensile adhesion strength after freeze/thaw cycles	≥ 1,0 N/mm²

8. Appropriate Technical Documentation and/or Specific Technical Documentation: Not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: ppa. Ulrich Köhler (General Manager)

Iphofen, on 2021-02-10