

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 2022/12/6 Revision date: 2022/12/6 Supersedes version of: 2020/3/3 Version: 12.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : FE-Imprägnierung Komponente A
Product code : 10229_0010

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use.
Use of the substance/mixture : For professional use only
Use of the substance/mixture : Two-pack reactive performance coatings for specific end use such as floors
Impregnation agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Knauf Gips KG
Am Bahnhof, 7
DE- 97346 Iphofen – Bayern
Germany
T +49 9323/31-0 - F +49 9323/31-277

zentrale@knauf.de - www.knauf.de

E-mail address of competent person responsible for the SDS : sds-info@knauf.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	GHS07	GHS09
Signal word (CLP)	: Warning	
Contains	: Bisphenol F-epoxy resin, reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2), Bis(4,4'-glycidylxyphenyl) propan	
Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.	
Precautionary statements (CLP)	: P273 - Avoid release to the environment. P280 - Wear protective gloves, protective clothing, eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.	
EUH-statements	: EUH205 - Contains epoxy constituents. May produce an allergic reaction.	
Extra phrases	: MAXIMUM VOC CONTENT LIMIT VALUES FOR PAINTS AND VARNISHES. Product Subcategory: j (Type: SB): 500 g/l. VOC content: < 0,5 % (< 5,7 g/l). The product is intended for professional use.	

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) (933999-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
3-glycidylxypropyltrimethoxysilane (2530-83-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis(4,4'-glycidylxyphenyl) propan	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-073-00-2 REACH-no: 01-2119456619-26	55 - < 60	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Bisphenol F-epoxy resin	CAS-No.: 9003-36-5 EC-No.: 500-006-8 REACH-no: 01-2119454392-40	20 - < 25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	CAS-No.: 933999-84-9 EC-No.: 618-939-5 REACH-no: 01-2119463471-41	15 - < 20	Skin Sens. 1, H317 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 3, H412
3-glycidyoxypropyltrimethoxysilane	CAS-No.: 2530-83-8 EC-No.: 219-784-2 REACH-no: 01-2119513212-58	1 - < 5	Eye Dam. 1, H318

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Bis(4,4'-glycidyoxyphenyl) propan	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-073-00-2 REACH-no: 01-2119456619-26	(5 ≤C < 100) Skin Irrit. 2, H315 (5 ≤C < 100) Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Protection for the first aid staff. Move the affected person away from the contaminated area. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
First-aid measures after inhalation	: Remove the victim into fresh air. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. When in doubt or if symptoms are observed, get medical advice.
First-aid measures after skin contact	: After contact with skin, wash immediately and thoroughly with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. Take victim to a doctor if irritation persists.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult an eye specialist.
First-aid measures after ingestion	: Rinse mouth. Drink plenty of water. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO ₂). Foam. extinguishing powder. Adapt extinguishing media to the environment.
Unsuitable extinguishing media	: high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not flammable.
-------------	------------------

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

- Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing. Full suit.
Other information : Use water spray to disperse the vapours. Do not dispose of fire-fighting water in the environment. Prevent entry to sewers and public waters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate air ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not flush into surface water or sewer system.

6.3. Methods and material for containment and cleaning up

- For containment : Contain the spilled material by bunding.
Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). For further information refer to section 13.

6.4. Reference to other sections

See Section 7. See Section 8. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed. Store in a place accessible by authorised persons only. Use appropriate ventilation. Keep only in original container. Store in a dry place.
Storage temperature : 10 – 30 °C
Information on mixed storage : TRGS 510: Storage of hazardous substances in non-stationary containers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Use appropriate ventilation. Do not breathe gas/fumes/vapour/spray.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Protective goggles

Eye protection			
Type	Field of application	Characteristics	Standard
Sealed safety goggles			

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
safety foot-wear	EN ISO 20345
Wear long sleeves	
Rubber apron, boots	EN 14605

Hand protection:

Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves, Long term exposure	Viton	2 (> 30 minutes)	0,4		EN ISO 374

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves, Short term exposure, Splash guard	Butyl rubber, Nitrile rubber (NBR)		0,4		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

No respiratory protection needed under normal use conditions

Respiratory protection			
Device	Filter type	Condition	Standard
Breathing apparatus with filter	Type A - High-boiling (>65 °C) organic compounds	Vapour protection	EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Do not breathe gas/fumes/vapour/spray. Take off immediately all contaminated clothing. Skin protection. Do not eat, drink or smoke when using this product. Always wash hands and face immediately after handling this product, and once again before leaving the workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Transparent.
Appearance	: Liquid.
Odour	: Mild odour.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 510 – 770 mPa.s (25 °C, ISO 2884-1)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: ≈ 1,14 g/cm ³ (23 °C, ISO 2811-2)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 0,5 % (< 5,7 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Bisphenol F-epoxy resin (9003-36-5)	
LD50 oral rat	> 2000 mg/kg
reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) (933999-84-9)	
LD50 oral rat	2189 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 15 day(s))
ATE CLP (oral)	2189 mg/kg bodyweight
3-glycidyloxypropyltrimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)
LD50 dermal rabbit	4250 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
LC50 Inhalation - Rat	> 5,3 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol))
ATE CLP (oral)	8025 mg/kg bodyweight
ATE CLP (dermal)	4250 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) (933999-84-9)

LC50 - Fish [1]	30 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	39 – 57 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

3-glycidyoxypropyltrimethoxysilane (2530-83-8)

LC50 - Fish [1]	55 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value)
LC50 - Fish [2]	237 mg/l (96 h, Salmo gairdneri, Static system, Literature study, Young)
EC50 - Crustacea [1]	473 – 710 mg/l (48 h, Daphnia magna, Literature study)
ErC50 algae	350 mg/l (72 h, Selenastrum capricornutum, Literature study)

12.2. Persistence and degradability

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) (933999-84-9)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

3-glycidyoxypropyltrimethoxysilane (2530-83-8)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

Bis(4,4'-glycidyoxyphenyl) propan (1675-54-3)

Persistence and degradability	Biodegradability in water: no data available.
-------------------------------	---

12.3. Bioaccumulative potential

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) (933999-84-9)

Partition coefficient n-octanol/water (Log Pow)	0,822 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

3-glycidyoxypropyltrimethoxysilane (2530-83-8)

Partition coefficient n-octanol/water (Log Pow)	-0,92 (Estimated value)
Bioaccumulative potential	Not bioaccumulative.

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Bis(4,4'-glycidyoxyphenyl) propan (1675-54-3)

Bioaccumulative potential Not bioaccumulative.

12.4. Mobility in soil

reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) (933999-84-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 2,98 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)

Ecology - soil Low potential for adsorption in soil.

3-glycidyoxypropyltrimethoxysilane (2530-83-8)

Ecology - soil No (test)data on mobility of the substance available.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations : Prevent liquid from entering sewers, watercourses, underground or low areas. Dispose as hazardous waste.
Additional information : Avoid sub-soil penetration. Disposal must be done according to official regulations.
European List of Waste (LoW) code : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 3082
UN-No. (IMDG) : UN 3082
UN-No. (IATA) : UN 3082
UN-No. (ADN) : UN 3082
UN-No. (RID) : UN 3082

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)
Proper Shipping Name (ADN) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)
Proper Shipping Name (RID) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)

14.3. Transport hazard class(es)

ADR


Transport hazard class(es) (ADR) : 9

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878


Danger labels (ADR) : 9



IMDG

Transport hazard class(es) (IMDG) : 9


Danger labels (IMDG) : 9



IATA

Transport hazard class(es) (IATA) : 9


Danger labels (IATA) : 9



ADN

Transport hazard class(es) (ADN) : 9


Danger labels (ADN) : 9



RID

Transport hazard class(es) (RID) : 9

Danger labels (RID) : 9



14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : III

Packing group (IATA) : III

Packing group (ADN) : III

Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : M6

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E1

Transport category (ADR) : 3

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Orange plates : 

Tunnel restriction code (ADR) : -

Transport by sea

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E1

Air transport

PCA Excepted quantities (IATA) : E1

PCA limited quantity max net quantity (IATA) : 30kgG

Inland waterway transport

Classification code (ADN) : M6

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Rail transport

Classification code (RID) : M6

Limited quantities (RID) : 5L

Excepted quantities (RID) : E1

Transport category (RID) : 3

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

VOC content : < 0,5 % (< 5,7 g/l)

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : E2

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

FE-Imprägnierung Komponente A

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Other information

: Technical information service (see point 1):

A call to Knauf Direkt will be charged at 0.39 € per minute. Callers, the telephone numbers of whom are not saved in the Knauf Gips KG address database, e.g. private property owners or noncustomers, will pay 1.69 € per minute from the German network. Callers using mobile telephones will be charged according to the network provider and tariff.

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH205	Contains epoxy constituents. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1

Knauf SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 2022/12/6 Revision date: 2022/12/6 Supersedes version of: 2020/3/3 Version: 12.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : FE-Imprägnierung Komponente B
Product code : 10229_0010

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use.
Use of the substance/mixture : For professional use only
Use of the substance/mixture : Hardener

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Knauf Gips KG
Am Bahnhof, 7
DE- 97346 Iphofen – Bayern
Germany
T +49 9323/31-0 - F +49 9323/31-277
zentrale@knauf.de - www.knauf.de
E-mail address of competent person responsible for the SDS : sds-info@knauf.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute Tox. 4 (Oral)	H302
Skin Corr. 1	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

	GHS05	GHS07	GHS09
Signal word (CLP)	: Danger		
Contains	: Phenol, styrenated , propylidynetrimethanol, propoxylated, reaction products with ammonia, 1,3-Benzenedimethanamine, 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Hazard statements (CLP)	: H302 - Harmful if swallowed. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.		
Precautionary statements (CLP)	: P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor.		
EUH-statements	: EUH071 - Corrosive to the respiratory tract.		
Extra phrases	: MAXIMUM VOC CONTENT LIMIT VALUES FOR PAINTS AND VARNISHES. Product Subcategory: j (Type: SB): 500 g/l. VOC content: < 0,5 % (< 5,15 g/l). The product is intended for professional use.		

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Phenol, styrenated (61788-44-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Phenol, styrenated	CAS-No.: 61788-44-1 EC-No.: 262-975-0 REACH-no: 01-2119980970-27	40 - < 45	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
propylidynetrimethanol, propoxylated, reaction products with ammonia	CAS-No.: 39423-51-3 EC-No.: 500-105-6 REACH-no: 01-2119556886-20	30 - < 35	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Aquatic Chronic 2, H411

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,3-Benzenedimethanamine	CAS-No.: 1477-55-0 EC-No.: 216-032-5	15 - < 20	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
3-aminomethyl-3,5,5-trimethylcyclohexylamine	CAS-No.: 2855-13-2 EC-No.: 220-666-8 EC Index-No.: 612-067-00-9 REACH-no: 01-2119514687-32	10 - < 15	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Protection for the first aid staff. Move the affected person away from the contaminated area. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
First-aid measures after inhalation	: In case of accident by inhalation: remove casualty to fresh air and keep at rest. When in doubt or if symptoms are observed, get medical advice.
First-aid measures after skin contact	: After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Take medical advice.
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth out with water. Drink plenty of water. Do NOT induce vomiting. Potential adverse human health effects and symptoms. Gastric perforation. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Adapt extinguishing media to the environment. Carbon dioxide (CO ₂). Foam. extinguishing powder.
Unsuitable extinguishing media	: high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not flammable.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Use water spray to disperse the vapours. Do not dispose of fire-fighting water in the environment. Prevent entry to sewers and public waters.

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use appropriate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothing. Wear personal protective equipment.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). For further information refer to section 13.

6.4. Reference to other sections

See Section 7. See Section 8. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wear personal protective equipment. Do not breathe gas/fumes/vapour/spray.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Store in a place accessible by authorised persons only. Use appropriate ventilation. Keep in original containers. Store in a dry place.
Storage temperature : 10 – 30 °C
Information on mixed storage : TRGS 510: Storage of hazardous substances in non-stationary containers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means. Do not breathe gas/fumes/vapour/spray.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Protective goggles

Eye protection			
Type	Field of application	Characteristics	Standard
Sealed safety goggles			

8.2.2.2. Skin protection

Skin and body protection:

safety foot-wear. Rubber apron, boots. Long sleeved protective clothing

Skin and body protection	
Type	Standard
safety foot-wear	EN ISO 20345
Rubber apron, boots	EN 14605

Hand protection:

Impermeable protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves, Long term exposure	Viton	2 (> 30 minutes)	0,4		EN ISO 374
Chemically resistant protective gloves, Short term exposure, Splash guard	Butyl rubber, Nitrile rubber (NBR)		0,4		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Approved organic vapour respirator

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Respiratory protection			
Device	Filter type	Condition	Standard
Breathing apparatus with filter	Type A - High-boiling (>65 °C) organic compounds	In case of inadequate ventilation wear respiratory protection, Vapour protection	EN 14387

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not drink, eat or smoke in the workplace. Always wash hands and face immediately after handling this product, and once again before leaving the workplace. Take off immediately all contaminated clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Odour	: Amine-like.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not available
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 112 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 310 – 465 mPa.s (ISO 2884-1)
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: ≈ 1,03 g/cm ³ (ISO 2811-2)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 0,5 % (< 5,15 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Acids. Oxidizing agent.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

FE-Imprägnierung Komponente B	
ATE CLP (oral)	1173,4 mg/kg bodyweight
Phenol, styrenated (61788-44-1)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Skin, 14 day(s))
LC50 Inhalation - Rat	> 4,92 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
propylidynetrimehanol, propoxylated, reaction products with ammonia (39423-51-3)	
LD50 oral rat	550 mg/kg (Rat)
LD50 dermal rabbit	401 mg/kg (Rabbit)
ATE CLP (oral)	500 mg/kg bodyweight
ATE CLP (dermal)	1100 mg/kg bodyweight
1,3-Benzenedimethanamine (1477-55-0)	
ATE CLP (oral)	500 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	11 mg/l/4h
ATE CLP (dust,mist)	1,5 mg/l/4h
3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
LD50 oral rat	1030 mg/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
LC50 Inhalation - Rat	> 5,01 mg/l (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Inhalation (aerosol), 14 day(s))
ATE CLP (oral)	1030 mg/kg bodyweight
ATE CLP (dermal)	1100 mg/kg bodyweight

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

Phenol, styrenated (61788-44-1)	
LC50 - Fish [1]	5,6 mg/l (96 h, Pisces, Experimental value)
EC50 - Crustacea [1]	4,6 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
EC50 72h - Algae [1]	0,326 mg/l (Algae, Literature study)
Threshold limit - Algae [1]	0,326 mg/l (EC50; 72 h; Algae)
Threshold limit - Algae [2]	0,14 mg/l (NOEC; 72 h; Algae)

propylidyntrimethanol, propoxylated, reaction products with ammonia (39423-51-3)	
EC50 - Crustacea [1]	13 mg/l 48 h; Daphnia magna (OECD 202)
ErC50 algae	4,4 mg/l 72 h; Pseudokirchnerella subcapitata (OECD 201)

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
LC50 - Fish [1]	110 mg/l (EU Method C.1, 96 h, Leuciscus idus, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	23 mg/l 48 h; Daphnia magna (OECD 202)
EC50 72h - Algae [1]	37 mg/l (EU Method C.3, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Cell numbers)
ErC50 algae	37 mg/l 72 h; Desmodesmus subspicatus

12.2. Persistence and degradability

Phenol, styrenated (61788-44-1)	
Persistence and degradability	Not readily biodegradable in water.

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

propylidynetrimehanol, propoxylated, reaction products with ammonia (39423-51-3)

Persistence and degradability Biodegradability in water: no data available.

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Persistence and degradability Not readily biodegradable in water.

12.3. Bioaccumulative potential

Phenol, styrenated (61788-44-1)

BCF - Fish [1] 3246 l/kg (BCFBAF v3.01, Pisces, Fresh water, Weight of evidence, Fresh weight)

Partition coefficient n-octanol/water (Log Pow) 3,03 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 23.6 °C)

Bioaccumulative potential Potential for bioaccumulation ($500 \leq \text{BCF} \leq 5000$).

propylidynetrimehanol, propoxylated, reaction products with ammonia (39423-51-3)

Bioaccumulative potential No bioaccumulation data available.

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

BCF - Fish [1] 1,827 – 3,16 (BCFBAF v3.01, Pisces, Estimated value)

Partition coefficient n-octanol/water (Log Pow) 0,99 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 23 °C)

Bioaccumulative potential Low potential for bioaccumulation ($\text{Log Kow} < 4$).

12.4. Mobility in soil

Phenol, styrenated (61788-44-1)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 3,145 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)

Ecology - soil Low potential for mobility in soil.

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

Surface tension 3470 mN/m (23 °C)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 2,97 (log Koc, QSAR)

Ecology - soil Low potential for adsorption in soil.

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not allow into drains or water courses.

Product/Packaging disposal recommendations : This material and its container must be disposed of as hazardous waste. Handle uncleaned empty containers as full ones.

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Additional information : Avoid sub-soil penetration. Disposal must be done according to official regulations.
European List of Waste (LoW) code : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 2735
UN-No. (IMDG) : UN 2735
UN-No. (IATA) : UN 2735
UN-No. (ADN) : UN 2735
UN-No. (RID) : UN 2735

14.2. UN proper shipping name

Proper Shipping Name (ADR) : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Proper Shipping Name (IMDG) : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Proper Shipping Name (IATA) : Polyamines, liquid, corrosive, n.o.s. (1,3-Benzenedimethanamine ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Proper Shipping Name (ADN) : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)
Proper Shipping Name (RID) : POLYAMINES, LIQUID, CORROSIVE, N.O.S. (1,3-Benzenedimethanamine ; 3-aminomethyl-3,5,5-trimethylcyclohexylamine)

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 8
Danger labels (ADR) : 8



IMDG

Transport hazard class(es) (IMDG) : 8
Danger labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : 8
Danger labels (IATA) : 8




ADN

Transport hazard class(es) (ADN) : 8
Danger labels (ADN) : 8

FE-Imprägnierung Komponente B


Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



RID

Transport hazard class(es) (RID) : 8
Danger labels (RID) : 8



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II
Packing group (ADN) : II
Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : Yes
Marine pollutant : Yes
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : C7
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E2
Transport category (ADR) : 2
Orange plates :



Tunnel restriction code (ADR) : E

Transport by sea

No data available

Air transport

PCA Excepted quantities (IATA) : E2
PCA limited quantity max net quantity (IATA) : 0.5L

Inland waterway transport

Classification code (ADN) : C7
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2

Rail transport

Classification code (RID) : C7
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Transport category (RID) : 2

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

VOC content : < 0,5 % (< 5,15 g/l)

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : E2

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

A chemical safety assessment has been carried out for the substance or the mixture by the supplier

SECTION 16: Other information

Other information : Technical information service (see point 1):
A call to Knauf Direkt will be charged at 0.39 € per minute. Callers, the telephone numbers of whom are not saved in the Knauf Gips KG address database, e.g. private property owners or noncustomers, will pay 1.69 € per minute from the German network. Callers using mobile telephones will be charged according to the network provider and tariff.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1	Skin corrosion/irritation, Category 1

FE-Imprägnierung Komponente B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

Knauf SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.