

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Steinsiegel
Product code : 12964_0022

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use. Professional use.
Use of the substance/mixture : Floor cleaner / floor polish

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Bauprodukte GmbH
Am Bahnhof, 7
DE- 97346 Iphofen – Bayern
Germany
T 09323 / 31-0

www.knauf.de/diy

E-mail address of competent person responsible for the SDS :

sdb@knauf.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
STOT SE 3	H336
Asp. Tox. 1	H304

Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H336 - May cause drowsiness or dizziness.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. P331 - Do NOT induce vomiting. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains isobutyl methacrylate, stabilised, 2-ethylhexyl methacrylate. May produce an allergic reaction.
Extra phrases	: VOC content: 75 % (607,5 g/L).

2.3. Other hazards

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
white mineral oil (petroleum) (8042-47-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
isobutyl methacrylate, stabilised (97-86-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-ethylhexyl methacrylate (688-84-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten	CAS-No.: 64742-48-9 EC-No.: 919-857-5	< 95	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
white mineral oil (petroleum)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 01-2119487078-27	< 15	Asp. Tox. 1, H304
isobutyl methacrylate, stabilised	CAS-No.: 97-86-9 EC-No.: 202-613-0 EC Index-No.: 607-113-00-X REACH-no: 01-2119488331-38	< 1	Flam. Liq. 3, H226 Skin Sens. 1, H317 Skin Irrit. 2, H315 STOT SE 3, H335

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-ethylhexyl methacrylate	CAS-No.: 688-84-6 EC-No.: 211-708-6 EC Index-No.: 607-134-00-4 REACH-no: 01-2119490166-35	< 1	Skin Sens. 1, H317 Aquatic Chronic 3, H412

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
2-ethylhexyl methacrylate	CAS-No.: 688-84-6 EC-No.: 211-708-6 EC Index-No.: 607-134-00-4 REACH-no: 01-2119490166-35	(10 ≤C < 100) STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove the victim into fresh air. If breathing stops, give artificial respiration. IN ALL CASES CONSULT A DOCTOR!.
- First-aid measures after skin contact : After contact with skin, wash immediately and thoroughly with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Consult an eye specialist.
- First-aid measures after ingestion : Rinse mouth out with water. Immediately give plenty of water. Never attempt to induce vomiting : risk of inhalation. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Headache. Giddiness. Respiratory difficulties. The liquid defats the skin.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Foam. Dry powder.
- Unsuitable extinguishing media : high volume water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable.
- Explosion hazard : Vapours may form explosive mixture with air.

5.3. Advice for firefighters

- Protection during firefighting : Self-contained breathing apparatus.
- Other information : Use water spray or fog for cooling exposed containers. Use water spray to disperse the vapours. Do not allow run-off from fire fighting to enter drains or water courses.

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove all sources of ignition. Ensure adequate air ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. If spilled, may cause the floor to be slippery.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not discharge the product into the environment. Be careful of explosion risk.

6.3. Methods and material for containment and cleaning up

For containment : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Disposal must be done according to official regulations.

6.4. Reference to other sections

7.1. Precautions for safe handling. For further information refer to section 13. 8. Exposure controls/personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : If handled uncovered, arrangements with local exhaust ventilation have to be used. Provide local exhaust or general room ventilation. Take precautionary measures against static discharge. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking. Vapours may form explosive mixture with air.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Take off immediately all contaminated clothing and wash it before reuse. Keep away from food, drink and animal feeding stuffs.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in a dry, cool area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a place accessible by authorised persons only.

Information on mixed storage : Do not store with: oxidizing agents. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Steinsiegel	
EU - Indicative Occupational Exposure Limit (IOEL)	
Regulatory reference	SCOEL Recommendations

8.1.2. Recommended monitoring procedures

No additional information available

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

If handled uncovered, arrangements with local exhaust ventilation have to be used.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear suitable protective clothing.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses, Face shield			

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)			

8.2.2.3. Respiratory protection

Respiratory protection:

Wear suitable respiratory equipment in case of insufficient ventilation

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Consumer exposure controls:

Do not breathe gas/fumes/vapour/spray.

Other information:

Do not eat, drink or smoke when using this product. Take off immediately all contaminated clothing. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: Not available

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Melting point	: Not determined
Freezing point	: Not available
Boiling point	: 155 °C
Flammability	: Not specifically applicable
Explosive limits	: Not available
Lower explosion limit	: 0,7 vol %
Upper explosion limit	: 6 vol %
Flash point	: 39 °C
Auto-ignition temperature	: Not specifically applicable
Decomposition temperature	: Not determined
pH	: Not determined
Viscosity, kinematic	: 1 mm ² /s
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not determined
Vapour pressure at 50°C	: Not available
Density	: 0,81 g/cm ³
Relative density	: Not available
Relative vapour density at 20°C	: Not determined
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 75 % (607,5 g/L)

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours may form explosive mixture with air.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified.

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

white mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 5 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Read-across, Inhalation (aerosol), 14 day(s))

isobutyl methacrylate, stabilised (97-86-9)	
LD50 oral rat	9590 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal	> 17760 mg/kg bodyweight (Guinea pig, Dermal)
ATE CLP (oral)	9590 mg/kg bodyweight

2-ethylhexyl methacrylate (688-84-6)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))

Skin corrosion/irritation	: Not classified pH: Not determined
Serious eye damage/irritation	: Not classified pH: Not determined
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

isobutyl methacrylate, stabilised (97-86-9)	
STOT-single exposure	May cause respiratory irritation.

Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cycloalkane, <2% Aromaten (64742-48-9)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

Steinsiegel	
Viscosity, kinematic	1 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

white mineral oil (petroleum) (8042-47-5)	
LC50 - Fish [1]	> 100 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

isobutyl methacrylate, stabilised (97-86-9)	
LC50 - Fish [1]	20 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 29 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, Locomotor effect)
ErC50 algae	16 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Fresh water, Experimental value, GLP)

2-ethylhexyl methacrylate (688-84-6)	
LC50 - Fish [1]	2,78 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oryzias latipes, Semi-static system, Fresh water, Experimental value, GLP)
EC50 - Crustacea [1]	0,85 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Weight of evidence)
EC50 - Crustacea [2]	4,56 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Weight of evidence)
ErC50 algae	7,68 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

Steinsiegel	
Persistence and degradability	This material has not been tested for environmental effects.

white mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water.

isobutyl methacrylate, stabilised (97-86-9)	
Persistence and degradability	Readily biodegradable in water.

2-ethylhexyl methacrylate (688-84-6)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2,66 g O ₂ /g substance

12.3. Bioaccumulative potential

Steinsiegel	
Bioaccumulative potential	No bioaccumulation data available.

white mineral oil (petroleum) (8042-47-5)	
BCF - Other aquatic organisms [1]	1216 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	5,18 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).

isobutyl methacrylate, stabilised (97-86-9)	
Partition coefficient n-octanol/water (Log Pow)	2,95 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

2-ethylhexyl methacrylate (688-84-6)	
BCF - Fish [1]	37 (OECD 305: Bioconcentration: Flow-Through Fish Test, 56 h, Danio rerio, Flow-through system, Fresh water, Experimental value, GLP)
Partition coefficient n-octanol/water (Log Pow)	4,95 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil

Steinsiegel

Ecology - soil This material has not been tested for environmental effects.

white mineral oil (petroleum) (8042-47-5)

Surface tension No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc) 2,64 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil Low potential for adsorption in soil.

isobutyl methacrylate, stabilised (97-86-9)

Surface tension No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc) 3,44 (log Koc, Calculated value)
Ecology - soil Low potential for mobility in soil.

2-ethylhexyl methacrylate (688-84-6)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 3,8 (log Koc, QSAR)
Ecology - soil Low potential for mobility in soil.

12.5. Results of PBT and vPvB assessment

Steinsiegel

PBT: not relevant – no registration required

vPvB: not relevant – no registration required

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No supplementary information available
Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Sewage disposal recommendations : Do not allow into drains or water courses.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Dirty containers cannot be handled as normal waste.
Additional information : This material and its container must be disposed of as hazardous waste.
European List of Waste (LoW) code : 20 01 13* - solvents
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR) : UN 3295
UN-No. (IMDG) : UN 3295

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

UN-No. (IATA) : UN 3295
UN-No. (ADN) : UN 3295
UN-No. (RID) : UN 3295

14.2. UN proper shipping name

Proper Shipping Name (ADR) : HYDROCARBONS, LIQUID, N.O.S.
Proper Shipping Name (IMDG) : HYDROCARBONS, LIQUID, N.O.S.
Proper Shipping Name (IATA) : Hydrocarbons, liquid, n.o.s.
Proper Shipping Name (ADN) : HYDROCARBONS, LIQUID, N.O.S.
Proper Shipping Name (RID) : HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : III
Packing group (IMDG) : III
Packing group (IATA) : III
Packing group (ADN) : III

Steinsiegel

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing group (RID) : III

14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Transport category (ADR) : 3
Orange plates :



Tunnel restriction code (ADR) : D/E

Transport by sea

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1

Air transport

PCA Excepted quantities (IATA) : E1
PCA limited quantity max net quantity (IATA) : 10L

Inland waterway transport

Classification code (ADN) : F1
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1

Rail transport

Classification code (RID) : F1
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Transport category (RID) : 3

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)
Contains no substance(s) listed on the REACH Candidate List
Contains no substance(s) listed on REACH Annex XIV (Authorisation List)
Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)
Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)
Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)
Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)
VOC content : 75 % (607,5 g/L)
Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains isobutyl methacrylate, stabilised, 2-ethylhexyl methacrylate. May produce an allergic reaction.
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Knauf SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.