

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 2023/3/29 Revision date: 2022/4/22 Supersedes version of: 2022/4/12 Version: 2.1



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : AQUAPANEL® Fugenkleber
Product code : 26012_0022

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use. Consumer use.
Use of the substance/mixture : Adhesive

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Knauf Bauprodukte GmbH & Co. KG
Am Bahnhof, 7
DE- 97346 Iphofen – Bayern
Germany
T 09323 / 31-0
sds-info@knauf.com - www.knauf.de/diy

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.
EUH-statements : EUH210 - Safety data sheet available on request.
Extra phrases : VOC content: 0 g/l.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
trimethoxyvinylsilane (2768-02-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
3-aminopropyltrimethoxysilane (13822-56-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
trimethoxyvinylsilane	CAS-No.: 2768-02-7 EC-No.: 220-449-8 REACH-no: 01-2119513215-52	1-5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Sens. 1B, H317
3-aminopropyltrimethoxysilane	CAS-No.: 13822-56-5 EC-No.: 237-511-5 REACH-no: 01-2119510159-45	1-<3	Eye Dam. 1, H318 Skin Irrit. 2, H315

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: First aider: Pay attention to self-protection!. Do not give an unconscious person anything to drink. Symptoms may be delayed.
First-aid measures after inhalation	: Move the affected person away from the contaminated area. Remove victim to fresh air. If necessary seek medical advice.
First-aid measures after skin contact	: Wash with plenty of soap and water. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention. Do not use : solvents, Thinner.
First-aid measures after eye contact	: Contact lenses should be removed. Rinse opened eye for several minutes under running water. Then consult doctor.
First-aid measures after ingestion	: Rinse mouth thoroughly with water. Do NOT induce vomiting. Immediately consult a doctor/medical service.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. extinguishing powder. Water spray. MAJOR FIRE: Alcohol-resistant foam.
Unsuitable extinguishing media	: No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂). Sulphur oxides. Nitrogen oxides. Toxic gases.
--	---

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters

- Protection during firefighting : Wear personal protective equipment. Self-contained breathing apparatus. Full suit.
Other information : In case of fire and/or explosion do not breathe fumes. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use appropriate ventilation. Remove all sources of ignition. Avoid dust production. Avoid contact with skin and eyes. If spilled, may cause the floor to be slippery.

6.1.1. For non-emergency personnel

- Protective equipment : Concerning personal protective equipment to use, see section 8.
Emergency procedures : Keep public away from danger area.

6.1.2. For emergency responders

- Protective equipment : Concerning personal protective equipment to use, see section 8.

6.2. Environmental precautions

Contain the spilled material by bunding. Stop leak if safe to do so. Prevent soil and water pollution. Avoid direct discharge into drains. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Mechanically recover the product. Dispose of in accordance with relevant local regulations.

6.4. Reference to other sections

See Section 8. See Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : On contact with water: May release : 22. Methanol.
Precautions for safe handling : Ensure adequate ventilation. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Keep away from food, drink and animal feedingstuffs. Contaminated work clothing should not be allowed out of the workplace. Do not drink, eat or smoke in the workplace. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in original container. Keep container tightly closed. Keep cool. Store under dry conditions.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Exposure limit values for the other components

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

methanol (67-56-1)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Methanol	Contact with water
IOEL TWA	260 mg/m ³	Contact with water
IOEL TWA [ppm]	200 ppm	Contact with water
Remark	skin	Contact with water
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC	Contact with water

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Provide adequate general and local exhaust ventilation. Use engineering controls to keep exposures below the OEL or DNEL. Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Protective goggles (EN 166)

8.2.2.2. Skin protection

Skin and body protection:

Use protective clothing

Skin and body protection	
Type	Standard
safety foot-wear	EN ISO 20345
Long sleeved protective clothing	

Hand protection:

Barrier cream. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	4 (> 120 minutes)	0.35		EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

If the ventilation is suitable, it is not essential to wear respiratory equipment. If the occupational exposure limit is exceeded: Suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Consumer exposure controls:

Use appropriate ventilation. Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feedingstuffs. Contaminated work clothing should not be allowed out of the workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Beige.
Appearance	: Pasty.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Flammable
Explosive properties	: Product is not explosive.
Oxidising properties	: Not oxidising.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 98 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Water: Insoluble
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: ≈ 1,6 g/cm ³ (20 °C)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 0 g/l

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

Reacts with water.

10.4. Conditions to avoid

Heat. Moisture.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Reacts with water. Methanol.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

AQUAPANEL® Fugenkleber	
LC50 Inhalation - Rat	> 20 mg/l/4h
ATE CLP (vapours)	> 20 mg/l/4h
trimethoxyvinylsilane (2768-02-7)	
LD50 oral rat	7120 – 7236 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	3259 – 3880 mg/kg bodyweight (Equivalent or similar to OECD 402, 24 h, Rabbit, Female, Converted value, Dermal, 14 day(s))
LC50 Inhalation - Rat	16,8 mg/l (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE CLP (oral)	7120 mg/kg bodyweight
ATE CLP (dermal)	3259 mg/kg bodyweight
ATE CLP (gases)	4500 ppmv/4h
ATE CLP (vapours)	16,8 mg/l/4h
ATE CLP (dust,mist)	1,5 mg/l/4h
3-aminopropyltrimethoxysilane (13822-56-5)	
LD50 oral rat	2,97 ml/kg (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	11,3 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat [ppm]	> 5 ppm (OECD 403: Acute Inhalation Toxicity, 6 h, Rat, Male, Read-across, Inhalation (vapours), 14 day(s))

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3-aminopropyltrimethoxysilane (13822-56-5)	
ATE CLP (oral)	3050,19 mg/kg bodyweight
ATE CLP (dermal)	11605,1 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified (Expert judgement)
Respiratory or skin sensitisation	: Not classified. ((OECD 429 method). LLNA. Expert judgement)
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

trimethoxyvinylsilane (2768-02-7)	
LC50 - Fish [1]	191 mg/l (96 h, Oncorhynchus mykiss, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	168,7 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	> 89 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

3-aminopropyltrimethoxysilane (13822-56-5)	
LC50 - Fish [1]	> 934 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Danio rerio, Semi-static system, Fresh water, Read-across, GLP)
EC50 - Crustacea [1]	331 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Read-across, GLP)
EC50 72h - Algae [1]	> 1000 mg/l (EU Method C.3, Desmodesmus subspicatus, Static system, Fresh water, Read-across, GLP)

12.2. Persistence and degradability

trimethoxyvinylsilane (2768-02-7)	
Persistence and degradability	Not readily biodegradable in water.

3-aminopropyltrimethoxysilane (13822-56-5)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

trimethoxyvinylsilane (2768-02-7)	
Partition coefficient n-octanol/water (Log Pow)	1,1 (QSAR, KOWWIN, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3-aminopropyltrimethoxysilane (13822-56-5)

Partition coefficient n-octanol/water (Log Pow)	0,2 (QSAR, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

trimethoxyvinylsilane (2768-02-7)

Ecology - soil	No (test)data on mobility of the substance available.
----------------	---

3-aminopropyltrimethoxysilane (13822-56-5)

Ecology - soil	No (test)data on mobility of the substance available.
----------------	---

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Combustion plant. Landfill. Disposal must be done according to official regulations.
Sewage disposal recommendations	: Do not discharge into drains.
Product/Packaging disposal recommendations	: Empty remaining contents. May be reused following decontamination. Handle uncleaned empty containers as full ones. Disposal must be done according to official regulations.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: Not applicable
----------------------------------	------------------

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

VOC content : 0 g/l

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

AQUAPANEL® Fugenkleber

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B

Knauf SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.