



DECLARATION OF PERFORMANCE

No 0010_Knauf_Direktabhänger_für_CD_60-27_C3_2023-01-30

1. Unique identification code of the product-type: **Suspension component – Knauf Direktabhänger für CD 60/27 C3**
2. Intended use/es: **suspended ceiling substructure component for use internally in buildings**
3. Manufacturer: **Knauf Gips KG | Am Bahnhof 7 | D-97346 Iphofen**
Tel: **+49 (9323) 31-0**
Fax: **+49 (9323) 31-277**
e-mail: **zentrale@knauf.de**
4. Authorised representative: **not relevant**
5. System/s of AVCP: **System 3 for load bearing capacity**
System 4 for other characteristics
6. a) Harmonised standard: **EN 13964:2014**
Notified body/ies: **TÜV Rheinland LGA Bautechnik (NB 0780) for load-bearing capacity**
6. b) European Assessment Document: **not relevant**
European Technical Assessment: **not relevant**
Technical Assessment Body: **not relevant**
Notified body/ies: **not relevant**
7. Declared performance/s:

Essential characteristics		Performance
Reaction to fire	R2F	A1
Load bearing capacity *		
- Substructure		NPD
- Suspension components and fasteners		400 N
- Top fixing of suspension components and perimeter trim fixings		NPD
- Tolerances and dimensions		pass
Resistance to fixings		NPD
Durability		class C
Dangerous substances	DS	NPD

* Respect the load-bearing capacity of further components of the substructure including the anchoring on the building structure.

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **not relevant**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Iphofen, 2023-01-30

i. V. Dr. Wolfgang Rümmler
(Head of Research & Development CE | Knauf Gips KG)

i. V. Dipl. Ing. (FH) | MBA & Eng. Michael Viebahn
(Head of Research & Development Competence Center Profile & Assembly Technology | Knauf Gips KG)