



DECLARATION OF PERFORMANCE

No 0010_Knauf_UA-Profil_50-40-2_2021-07-01

1. Unique identification code of the product-type: **U/40/48,8/40 – Knauf UA-Profil 50/40/2**
2. Intended use/es: **Metal framing components for gypsum plasterboard systems**
3. Manufacturer: **Knauf Gips KG | Am Bahnhof 7 | D-97346 Iphofen**
Tel: **+49 (9323) 31-0**
Fax: **+49 (9323) 31-277**
e-mail: **zentrale@knauf.de**
4. Authorised representative: **not relevant**
5. System/s of AVCP: **System 4**
6. a) Harmonised standard: **EN 14195:2005/AC:2006**
Notified body/ies: **not relevant**
6. b) European Assessment Document: **not relevant**
European Technical Assessment: **not relevant**
Technical Assessment Body: **not relevant**
Notified body/ies: **not relevant**
7. Declared performance/s:

Essential characteristics		Performance
Reaction to fire	R2F	A1
Yield strength	σ	250 N/mm ²
Dangerous substances	DS	NPD
8. Appropriate Technical Documentation and/or Specific Technical Documentation: **not relevant**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Iphofen, 2021-07-01

i. V. Dr. Wolfgang Rümmler
(Head of Research & Development D/CH | Knauf Gips KG)

i. V. Dipl. Ing. (FH) | MBA & Eng. Michael Viebahn
(Head of Drywall Systems D/CH | Knauf Gips KG)